



Product Technical Specifications

Mod. SG

Latex insulated gloves

Functionality

Insulated gloves are one of the most important pieces of PPE for working in the electrical sector. They are the first line of defense for contact with any live component or cable.

Product Features

The natural latex base has excellent dielectric properties. The thicker the glove, the greater the electrical resistance. The ergonomic design provides comfort and a smoother feel and allows the glove to be put on and taken off very easily.

Mechanical Features

Average tensile strength: **≥ 16 MPa**

Average elongation at break: **≥ 600%**

Puncture resistance: **≥ 18N/mm**

Tension set: **≥ 15%**





Mod. SG

Latex insulated gloves

Thermal characteristics

Resistance to very low temperatures:

Conditioning of the gloves for **24 hours at -40 °C. ± 3°C.**

Flame-retardant test: **Application of a flame for 10 seconds at a fingertip.**

Special features

Resistance to acid: **Conditioning of gloves by immersion for 8 hours at 23 ± 2 °C in a sulphuric acid solution at 32° Baume.**

Resistance to oil: **Conditioning by immersion in oil for 24 hours at 70 ± 2 °C.**

Resistance to ozone: **Conditioning of gloves in a chamber for 3 hours at 40 ± 2°C and in a 1 mg / m³ ozone concentration.**

Certified

According to the Standards:

IEC 60903:2014

UNE-EN 60903:2005

CE mark

Resistance to very low temperatures: **Conditioning of gloves for 24 hours at -40 ± 3°C.**

Specifications / Technical Data

Ref.	Class	Size	Length (mm)	Categories	Working Voltage (V) max.	Proof test Voltage (V) max.	Withstand Voltage (V) max.
SG-25 T9 SG-25 T10	00	9 10	360	AZC	500 V AC	2.500 V AC	5.000 V AC
SG-50 T9 SG-50 T10	0	9 10		AZC	1.000 V AC	5.000 V AC	10.000 V AC
SG-10 T9 SG-10 T10	1	9 10		RC	7.500 V AC	10.000 V AC	20.000 V AC
SG-20 T9 SG-20 T10	2	9 10		RC	17.000 V AC	20.000 V AC	30.000 V AC
SG-30 T9 SG-30 T10	3	9 10		RC	26.500 V AC	30.000 V AC	40.000 V AC
SG-40 T9 SG-40 T10	4	10 11	410	RC	36.000 V AC	40.000 V AC	50.000 V AC

Datos sujetos a cambios
2021, noviembre 24

Versión: R2-7.2 COM01

© 2017 Sofamel SLU
Todos los derechos reservados.

Las especificaciones están sujetas a cambios sin previo aviso.